


REV	DESCRIPTION	DESIGN	DATE
A	NEW RELEASE	Z.M.Xue	2023.12.23

Specifications:
Contact resistance:≤10mΩ
Insulation resistance:≥100MΩ
Withstand Voltage:1100V AC/minute
Rated voltage:50V AC DC
Rated current:3.5A AC DC
Temperature Range:-40℃~ +105℃
Housing:LCP UL94V-0,NATURAL
Contacts:BRASS/MATTE Sn-plated



ORDER INFORMATION:

QA2506AWR-03-F1CB3-R

PART No.

No.OF CIRCUITS:

PLASTIC MATERIAL:

F1C=LCP NATURAL

PACKAGING:
R=REEL

METAL CODE:
3=BRASS

PLATING:
B=MATTE Sn

JKUN 温州健坤接插件有限公司 WENZHOU JKUN CONNECTOR CO.,LTD.			TITLE: -	
GENERAL TOLERANCE		USE: CUSTOMER	PART NO.:	
X.X ±0.30	X. ±5°		QA2506AWR-03-F1CB3-R	
X.XX ±0.20	X.X ±2°	APPD: J.J.Yao	DWG NO.:	
X.XXX ±0.10	X.XX ±1°	CHKD: X.F.Yan	JKUN-GCKH-1569	
	UNITS: mm	DR: Z.M.Xue	SCALE	SHEET
			3 : 1	1 / 1

